

NL17SG125

Bus Buffer with 3-State Output

The NL17SG125 MiniGate™ is an advanced high-speed CMOS Bus Buffer with 3-State Output in ultra-small footprint.

The NL17SG125 input structures provides protection when voltages up to 4.6 V are applied.

Features

- Wide Operating V_{CC} Range: 0.9 V to 3.6 V
- High Speed: $t_{PD} = 2.4$ ns (Typ) at $V_{CC} = 3.0$ V, $C_L = 15$ pF
- Low Power Dissipation: $I_{CC} = 0.5$ μ A (Max) at $T_A = 25^\circ$ C
- 4.6 V Overvoltage Tolerant (OVT) Input Pins
- Ultra-Small Packages
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant




Figure 1. SOT-953
(Top Thru View)




Figure 2. SC-88A
(Top View)




Figure 3. UDFN6
(Top View)



Figure 4. Logic Symbol

PIN ASSIGNMENT

| Pin Number | SOT-953 | SC-88A | UDFN6 |
|------------|---------|--------|-------|
| 1 | IN A | OE | OE |
| 2 | GND | IN A | IN A |
| 3 | OE | GND | GND |
| 4 | OUT Y | OUT Y | OUT Y |
| 5 | VCC | VCC | NC |
| 6 | | | VCC |



ON Semiconductor®


<http://onsemi.com>

MARKING DIAGRAMS




SOT-953
CASE 527AE

F = Specific Device Code
(F with 90 degree clockwise rotation)
M = Month Code




UDFN6
1.0 x 1.0
CASE 517BX

K = Specific Device Code
(K with 270 degree clockwise rotation)
M = Month Code



UDFN6
1.45 x 1.0
CASE 517AQ

R = Specific Device Code
(R with 180 degree clockwise rotation)
M = Month Code



SC-88A
DF SUFFIX
CASE 419A

A4 = Device Code
M = Date Code*
▪ = Pb-Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.

FUNCTION TABLE

| A Input | OE Input | Y Output |
|---------|----------|----------|
| L | L | L |
| H | L | H |
| X | H | Z |

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

NL17SG125

MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|---------------|---|--|-------------|
| V_{CC} | DC Supply Voltage | -0.5 to +5.5 | V |
| V_{IN} | DC Input Voltage | -0.5 to +4.6 | V |
| V_{OUT} | DC Output Voltage Output at High or Low State Power-Down Mode ($V_{CC} = 0$ V) | -0.5 to $V_{CC} + 0.5$ -0.5 to +4.6 | V |
| I_{IK} | DC Input Diode Current $V_{IN} < GND$ | -20 | mA |
| I_{OK} | DC Output Diode Current $V_{OUT} < GND$ | -20 | mA |
| I_{OUT} | DC Output Source/Sink Current | ± 20 | mA |
| I_{CC} | DC Supply Current per Supply Pin | ± 20 | mA |
| I_{GND} | DC Ground Current per Ground Pin | ± 20 | mA |
| T_{STG} | Storage Temperature Range | -65 to +150 | $^{\circ}C$ |
| T_L | Lead Temperature, 1 mm from Case for 10 Seconds | 260 | $^{\circ}C$ |
| T_J | Junction Temperature Under Bias | +150 | $^{\circ}C$ |
| MSL | Moisture Sensitivity | Level 1 | |
| F_R | Flammability Rating Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in | |
| V_{ESD} | ESD Withstand Voltage Human Body Model (Note 2) Machine Model (Note 3) | >2000 >100 | V |
| $I_{LATCHUP}$ | Latchup Performance Above V_{CC} and Below GND at 125 $^{\circ}C$ (Note 4) | ± 100 | mA |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to EIA/JESD78.

RECOMMENDED OPERATING CONDITIONS

| Symbol | Characteristics | Min | Max | Unit |
|-----------------------|--|------------|-----------------|-------------|
| V_{CC} | Positive DC Supply Voltage | 0.9 | 3.6 | V |
| V_{IN} | Digital Input Voltage | 0.0 | 3.6 | V |
| V_{OUT} | Output Voltage Output at High or Low State Power-Down Mode ($V_{CC} = 0$ V) | 0.0 0.0 | V_{CC} 3.6 | V |
| T_A | Operating Temperature Range | -55 | +125 | $^{\circ}C$ |
| $\Delta t / \Delta V$ | Input Transition Rise or Fall Rate $V_{CC} = 3.3$ V \pm 0.3 V | 0 | 10 | ns/V |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

NL17SG125

DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Conditions | V _{CC} (V) | T _A = 25°C | | T _A = -55°C to +125°C | | Unit |
|-----------------|--------------------------------|---|---------------------------|-----------------------|--------------------------|----------------------------------|-----------------------|------|
| | | | | Min | Max | Min | Max | |
| | | | | V _{IH} | High-Level Input Voltage | | 0.9 | |
| | | | 1.1 to 1.3 | 0.7xV _{CC} | | 0.7xV _{CC} | | |
| | | | 1.4 to 1.6 | 0.65xV _{CC} | | 0.65xV _{CC} | | |
| | | | 1.65 to 1.95 | 0.65xV _{CC} | | 0.65xV _{CC} | | |
| | | | 2.3 to 2.7 | 1.7 | | 1.7 | | |
| | | | 3.0 to 3.6 | 2.0 | | 2.0 | | |
| V _{IL} | Low-Level Input Voltage | | 0.9 | | GND | | GND | V |
| | | | 1.1 to 1.3 | | 0.3xV _{CC} | | 0.3xV _{CC} | |
| | | | 1.4 to 1.6 | | 0.35xV _{CC} | | 0.35xV _{CC} | |
| | | | 1.65 to 1.95 | | 0.35xV _{CC} | | 0.35xV _{CC} | |
| | | | 2.3 to 2.7 | | 0.7 | | 0.7 | |
| | | | 3.0 to 3.6 | | 0.8 | | 0.8 | |
| V _{OH} | High-Level Output Voltage | V _{IN} = V _{IH} or V _{IL} | I _{OH} = -20 μA | 0.9 | 0.75 | | 0.75 | V |
| | | | I _{OH} = -0.3 mA | 1.1 to 1.3 | 0.75xV _{CC} | | 0.75xV _{CC} | |
| | | | I _{OH} = -1.7 mA | 1.4 to 1.6 | 0.75xV _{CC} | | 0.75xV _{CC} | |
| | | | I _{OH} = -3.0 mA | 1.65 to 1.95 | V _{CC} -0.45 | | V _{CC} -0.45 | |
| | | | I _{OH} = -4.0 mA | 2.3 to 2.7 | 2.0 | | 2.0 | |
| | | | I _{OH} = -8.0 mA | 3.0 to 3.6 | 2.48 | | 2.48 | |
| V _{OL} | Low-Level Output Voltage | V _{IN} = V _{IH} or V _{IL} | I _{OL} = 20 μA | 0.9 | | 0.1 | 0.1 | V |
| | | | I _{OL} = 0.3 mA | 1.1 to 1.3 | | 0.25xV _{CC} | 0.25xV _{CC} | |
| | | | I _{OL} = 1.7 mA | 1.4 to 1.6 | | 0.25xV _{CC} | 0.25xV _{CC} | |
| | | | I _{OL} = 3.0 mA | 1.65 to 1.95 | | 0.45 | 0.45 | |
| | | | I _{OL} = 4.0 mA | 2.3 to 2.7 | | 0.4 | 0.4 | |
| | | | I _{OL} = 8.0 mA | 3.0 to 3.6 | | 0.4 | 0.4 | |
| I _{IN} | Input Leakage Current | 0 ≤ V _{IN} ≤ 3.6 V | 0 to 3.6 | | | ±0.1 | | μA |
| I _{CC} | Quiescent Supply Current | V _{IN} = V _{CC} or GND | 3.6 | | | 1.0 | | μA |
| I _{OZ} | 3-State Output Leakage Current | V _{IN} = V _{IH} or V _{IL} V _{OUT} = 0 to 3.6 V | 0.9 to 3.6 | | | 1.0 | | μA |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NL17SG125

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns)

| Symbol | Parameter | Test Condition | V_{CC} (V) | $T_A = 25^\circ\text{C}$ | | | $T_A = -55^\circ\text{C to } +125^\circ\text{C}$ | | Unit | |
|--------------------------|---|--|--------------|--------------------------|------|------|--|------|------|----|
| | | | | Min | Typ | Max | Min | Max | | |
| t_{PLH} , t_{PHL} | Propagation Delay, A to Y | $C_L = 10$ pF, $R_L = 1$ M Ω | 0.9 | - | 11.3 | 13.6 | - | 15.9 | ns | |
| | | | 1.1 to 1.3 | - | 8.3 | 10.4 | - | 12.8 | | |
| | | | 1.4 to 1.6 | - | 5.0 | 8.5 | - | 10.0 | | |
| | | | 1.65 to 1.95 | - | 4.0 | 6.2 | - | 6.7 | | |
| | | | 2.3 to 2.7 | - | 2.6 | 3.9 | - | 4.4 | | |
| | | | 3.0 to 3.6 | - | 2.1 | 3.1 | - | 3.7 | | |
| | | $C_L = 15$ pF, $R_L = 1$ M Ω | 0.9 | - | 12.6 | 14.7 | - | 17.0 | ns | |
| | | | 1.1 to 1.3 | - | 9.6 | 11.5 | - | 15.2 | | |
| | | | 1.4 to 1.6 | - | 5.6 | 9.3 | - | 11.2 | | |
| | | | 1.65 to 1.95 | - | 4.5 | 6.9 | - | 7.1 | | |
| | | | 2.3 to 2.7 | - | 2.9 | 4.4 | - | 5.0 | | |
| | | | 3.0 to 3.6 | - | 2.4 | 3.4 | - | 3.9 | | |
| | | $C_L = 30$ pF, $R_L = 1$ M Ω | 0.9 | - | 14.5 | 16.3 | - | 19.6 | ns | |
| | | | 1.1 to 1.3 | - | 11.3 | 13.6 | - | 17.5 | | |
| | | | 1.4 to 1.6 | - | 8.2 | 13.1 | - | 15.9 | | |
| | | | 1.65 to 1.95 | - | 6 | 9.2 | - | 9.6 | | |
| | | | 2.3 to 2.7 | - | 4 | 5.7 | - | 6.1 | | |
| | | | 3.0 to 3.6 | - | 3.3 | 4.4 | - | 4.8 | | |
| t_{PZH} , t_{PZL} | Output Enable Time, \overline{OE} to Y | $C_L = 10$ pF; $R_L = 100$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω | | | | | | | ns | |
| | | | 0.9 | - | 11.0 | 13.3 | - | 15.8 | | |
| | | | 1.1 to 1.3 | - | 8.4 | 10.9 | - | 13.0 | | |
| | | | 1.4 to 1.6 | - | 5.3 | 7.8 | - | 8.3 | | |
| | | | 1.65 to 1.95 | - | 3.9 | 5.5 | - | 5.9 | | |
| | | | 2.3 to 2.7 | - | 2.5 | 3.5 | - | 3.8 | | |
| | | | 3.0 to 3.6 | - | 2.1 | 2.7 | - | 3 | | |
| | | $C_L = 15$ pF; $R_L = 100$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω | | | | | | | | ns |
| | | | 0.9 | - | 12.0 | 14.8 | - | 17.0 | | |
| | | | 1.1 to 1.3 | - | 9.0 | 11.7 | - | 13.8 | | |
| | | | 1.4 to 1.6 | - | 5.9 | 8.9 | - | 11 | | |
| | | | 1.65 to 1.95 | - | 4.4 | 6.3 | - | 6.5 | | |
| | | | 2.3 to 2.7 | - | 2.9 | 3.9 | - | 4.2 | | |
| | | $C_L = 30$ pF; $R_L = 100$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω | | | | | | | | ns |
| | | | 0.9 | - | 13.0 | 15.2 | - | 18.3 | | |
| | | | 1.1 to 1.3 | - | 10.0 | 13.1 | - | 15.2 | | |
| | | | 1.4 to 1.6 | - | 8.3 | 12.2 | - | 13.7 | | |
| | | | 1.65 to 1.95 | - | 6.1 | 8.6 | - | 9.7 | | |
| | | | 2.3 to 2.7 | - | 3.8 | 5 | - | 5.5 | | |
| | | | 3.0 to 3.6 | - | 2.9 | 3.8 | - | 4.2 | | |

NL17SG125

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns) (continued)

| Symbol | Parameter | Test Condition | V_{CC} (V) | $T_A = 25^\circ\text{C}$ | | | $T_A = -55^\circ\text{C to } +125^\circ\text{C}$ | | Unit | |
|--------------------------|---|--|--------------|--------------------------|-------|------|--|------|------|----|
| | | | | Min | Typ | Max | Min | Max | | |
| t_{PHZ} , t_{PLZ} | Output Disable Time, OE to Y | $C_L = 10$ pF; $R_L = 100$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω | | | | | | | ns | |
| | | | 0.9 | - | 100.4 | - | - | - | | |
| | | | 1.1 to 1.3 | - | 9.1 | 14.4 | - | 22.4 | | |
| | | | 1.4 to 1.6 | - | 7.1 | 9.1 | - | 10.4 | | |
| | | | 1.65 to 1.95 | - | 6.5 | 8.3 | - | 9 | | |
| | | | 2.3 to 2.7 | - | 5.8 | 7.3 | - | 8.8 | | |
| | | | 3.0 to 3.6 | - | 5.4 | 6.9 | - | 7.6 | | |
| | | $C_L = 15$ pF; $R_L = 100$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω | | | | | | | | ns |
| | | | 0.9 | - | 122.2 | - | - | - | | |
| | | | 1.1 to 1.3 | - | 9.8 | 15.3 | - | 25.1 | | |
| | | | 1.4 to 1.6 | - | 7.8 | 9.8 | - | 11.3 | | |
| | | | 1.65 to 1.95 | - | 7.2 | 9.2 | - | 10.6 | | |
| | | | 2.3 to 2.7 | - | 7 | 8.2 | - | 10.3 | | |
| | | | 3.0 to 3.6 | - | 6.6 | 7.7 | - | 9.5 | | |
| | | $C_L = 30$ pF; $R_L = 100$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω $R_L = 5$ k Ω | | | | | | | | ns |
| | | | 0.9 | - | 217.1 | - | - | - | | |
| | | | 1.1 to 1.3 | - | 13.2 | 19.6 | - | 31.9 | | |
| | | | 1.4 to 1.6 | - | 12.2 | 13.5 | - | 14.9 | | |
| | | | 1.65 to 1.95 | - | 11.4 | 12.7 | - | 13.9 | | |
| | | | 2.3 to 2.7 | - | 11.3 | 12.2 | - | 13.5 | | |
| | | | 3.0 to 3.6 | - | 10.2 | 11.5 | - | 12.9 | | |
| C_{IN} | Input Capacitance | | 0 to 3.6 | | 3 | - | - | - | pF | |
| C_O | Output Capacitance | $V_O = \text{GND}$ | 0 | | 3 | - | - | - | pF | |
| C_{PD} | Power Dissipation Capacitance (Note 5) | $f = 10$ MHz | 0.9 to 3.6 | - | 4 | - | - | - | pF | |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}$. C_{PD} is used to determine the no-load dynamic power consumption; $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$.

NL17SG125




Figure 5. Test Circuit




Figure 6. t_{pLH} , t_{pHL} Waveforms




Figure 7. t_{pLZ} , t_{pHZ} , t_{pZH} , t_{pZL} Waveforms

NL17SG125

ORDERING INFORMATION

| Device | Package | Shipping [†] |
|-------------------|--------------------------------|-----------------------|
| NL17SG125P5T5G | SOT-953 (Pb-Free) | 8000 / Tape & Reel |
| NL17SG125DFT2G | SC-88A (Pb-Free) | 3000 / Tape & Reel |
| NLV17SG125DFT2G* | SC-88A (Pb-Free) | 3000 / Tape & Reel |
| NL17SG125MU1TCG** | UDFN6 1.45 x 1 mm (Pb-Free) | 3000 / Tape & Reel |
| NL17SG125MU3TCG** | UDFN6 1 x 1 mm (Pb-Free) | 3000 / Tape & Reel |

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.




*NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

**In Development

NL17SG125

PACKAGE DIMENSIONS

SOT-953
CASE 527AE
ISSUE E




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| MILLIMETERS | | | |
|----------------|-----------|------|------|
| DIM | MIN | NOM | MAX |
| A | 0.34 | 0.37 | 0.40 |
| b | 0.10 | 0.15 | 0.20 |
| C | 0.07 | 0.12 | 0.17 |
| D | 0.95 | 1.00 | 1.05 |
| E | 0.75 | 0.80 | 0.85 |
| e | 0.35 BSC | | |
| H _E | 0.95 | 1.00 | 1.05 |
| L | 0.175 REF | | |
| L ₂ | 0.05 | 0.10 | 0.15 |
| L ₃ | --- | --- | 0.15 |

SOLDERING FOOTPRINT*




DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NL17SG125

PACKAGE DIMENSIONS

UDFN6 1.0x1.0, 0.35P
CASE 517BX
ISSUE O




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.20 MM FROM TERMINAL TIP.
4. PACKAGE DIMENSIONS EXCLUSIVE OF BURRS AND MOLD FLASH.

| MILLIMETERS | | |
|-------------|----------|------|
| DIM | MIN | MAX |
| A | 0.45 | 0.55 |
| A1 | 0.00 | 0.05 |
| A3 | 0.13 REF | |
| b | 0.12 | 0.22 |
| D | 1.00 BSC | |
| E | 1.00 BSC | |
| e | 0.35 BSC | |
| L | 0.25 | 0.35 |
| L1 | 0.30 | 0.40 |

RECOMMENDED SOLDERING FOOTPRINT*





*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


NL17SG125

PACKAGE DIMENSIONS

UDFN6 1.45x1.0, 0.5P
CASE 517AQ
ISSUE O



DETAIL A
OPTIONAL CONSTRUCTIONS




DETAIL B
OPTIONAL CONSTRUCTIONS

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm FROM THE TERMINAL TIP.

| MILLIMETERS | | |
|-------------|----------|------|
| DIM | MIN | MAX |
| A | 0.45 | 0.55 |
| A1 | 0.00 | 0.05 |
| A2 | 0.07 REF | |
| b | 0.20 | 0.30 |
| D | 1.45 BSC | |
| E | 1.00 BSC | |
| e | 0.50 BSC | |
| L | 0.30 | 0.40 |
| L1 | --- | 0.15 |

MOUNTING FOOTPRINT





DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NL17SG125

PACKAGE DIMENSIONS

SC-88A (SC-70-5/SOT-353)
CASE 419A-02
ISSUE L




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.071 | 0.087 | 1.80 | 2.20 |
| B | 0.045 | 0.053 | 1.15 | 1.35 |
| C | 0.031 | 0.043 | 0.80 | 1.10 |
| D | 0.004 | 0.012 | 0.10 | 0.30 |
| G | 0.026 BSC | | 0.65 BSC | |
| H | --- | 0.004 | --- | 0.10 |
| J | 0.004 | 0.010 | 0.10 | 0.25 |
| K | 0.004 | 0.012 | 0.10 | 0.30 |
| N | 0.008 REF | | 0.20 REF | |
| S | 0.079 | 0.087 | 2.00 | 2.20 |

SOLDER FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

MiniGate is a trademark of Semiconductor Components Industries, LLC (SCILLC).

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative